ActivePure

Wellness Begins with the Air You Breathe[™]

Features ActivePure® Technology, proven to reduce up to 99.9% of many common types of bacteria, viruses, and mold¹

THE TECHNOLOGY

The ActivePure® Modular Guardian utilizes ActivePure Technology in the form of a portable wall-mount unit for situations when an Induct unit cannot be installed or when air & surface protection is needed around-the-clock. Patented ActivePure Technology is an advanced air and surface purification technology that has been proven to reduce up to 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as a complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens:

• SARS-CoV-2

- Listeria monocytogenes
- Staphylococcus aureus
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia herbicola

- Murine Norovirus
- Aspergillus niger endospores • E. coli
 - Candida auris
 - Botrytis cinerea
 - Sclerotinia sclerotiorum
 - Legionella pneumophila
 - Aspergillus versicolor
 - Clostridium difficile
 - Salmonella enterica

THE BENEFITS

The ActivePure Modular Guardian provides 24/7 air purification and surface decontamination in indoor spaces up to 2,000 sq. ft. while the unit is running. It is a proactive and effective solution for your home or business.

- Uses ActivePure Technology, proven to reduce up to 99.9% of many common types of bacteria, viruses, and mold in indoor air and surfaces¹
- Reduces VOC gases, smoke and odors¹
- Easy installation
- Mounts on wall bracket
- Easy to move locations

Devices with ActivePure® Technology have been proven to reduce up to 6 of many common types of bacteria, viruses, and mold1



View test results at ActivePure.com/Scientific-Proof





Product Information	00783 Model: E200A - ZERO 020NE EMISSIONS - MEASURED 020NE Meets California ozone emissions limit. CARB Certified. - EMISSIONS FROM APCO Validated to UL 2998 - UL 2008
Technology Included	ActivePure® Technology – (1) Cell with (2) 14" Bulbs
Electrical	110-120V, 60 Hz .75A (90W)
Mechanical	100 CFM (Fan) 2.83 m ³ /min
	Motor: Impedance watts
Safety	Conforms to UL 867
Weight & Dimensions	12 lbs (5.44 kg)
	20" H x 20" W x 5.5" D (50.8 cm x 50.8 cm x 13.97 cm)
Recommended	Up to 2,000 sq. ft. (185.8 m²) or 1,000 sq. ft. (92.9 m²) in commercial environments, depending
Maximum Coverage in a	on occupant density and other factors.
Contiguous Space ¹	For coverage in medical or health care environments, contact Medical@activepure.com.
Warranty	Limited 5 year warranty

1. Recommended ceiling height to not exceed 10 ft.. Solutions should be customized based upon a variety of factors including HVAC system capabilities, HVAC settings, air flows (taking into account walls, air pressure, and doors), ambient air temperature, humidity, variable density, known VOC concentrations, and other layers of protection.

Let us show you more!



ActivePure Technology is available in HVAC, Induct units and portable, plug-and-play units.

